

angleIRON



**Models: UT48AE, UT410AE, UT58AE
(UT48AE shown)**

4' & 5' wide models: available in 8' & 10' bed lengths.
UT models feature a tilt-bed.

Standard features: 12" high sides, tip-away tongue jack, 2,000 lb. GAWR, 12" tires & wheels, 1" thick treated wood floor, 8 tie down points

Available options: metal mesh on sides and front



**Models: LT48AE, LT410AE, LT58AE, LT510AE
(LT48AE shown)**

4' & 5' wide models: available in 8' & 10' bed lengths. LT models feature a fold-down landscape gate.

Standard features: 12" high sides, tip-away tongue jack, 2,000 lb. GAWR, 12" tires & wheels, 1" thick treated wood floor, 8 tie down points

Available options: metal mesh on sides and front



Models: UT48A, UT410A, UT58A, UT510A, LT48A, LT410A, LT58A, LT510A (LT510A shown)

4' & 5' wide models: available in 8' & 10' bed lengths. LT models feature a fold-down landscape gate. UT models feature a tilt-bed.

Standard features: 16" high sides, tip-away tongue jack, 3,500 lb. GAWR, 14" tires & wheels, 1" thick treated wood floor, 8 tie down points

Available options: 24" high sides, metal mesh on sides and front, brakes



Models: UT6410A, UT6412A, UT6414A, LT6410A, LT6412A, LT6414A (LT6412A shown)

6'-4" wide single axle models: available in 10', 12', and 14' bed lengths. LT models feature a fold-down landscape gate. UT models feature a tilt-bed.

Standard features: 16" high sides, tip-away tongue jack, 3,500 lb. GAWR, 14" tires & wheels, 1-1/2" thick treated wood floor, 8 tie down points

Available options: 24" high sides, metal mesh on sides and front, brakes



Models: UT6412AT, UT6414AT, UT6416AT, LT6410AT, LT6412AT, LT6414AT (LT6416AT shown)

6'-4" wide tandem axle models: available in 12', 14', 16', and 18' bed lengths. LT models feature a fold-down landscape gate.

UT models feature slide-out ramps.
Standard features: 16" high sides, tip-away tongue jack, 7,000 lb. GCAWR, 14" tires & wheels, 1 electric brake axle, 1-1/2" thick treated wood floor, 8 tie down points

Available options: 24" high sides, metal mesh on sides and front, 2nd brake axle, 10,000 lb. GCAWR package

Visit us at www.mastertow.com

MASTERTOW

Angle Iron Trailer Features



A



B



C



D



E



F

- A** 4 Heavy Duty Tie Down Points On Each Side
- B** Easy To Use Spring Loaded Gate Latch
- C** Chrome Fender Trim & Accu-Lube Hubs
- D** Tip-Away Jack Mounted To Tubular A-Frame Tongue
- E** Pressure Treated Wood Flooring Boards
- F** Computer Balanced 14" Tires & Wheels

Model	Bed Width	Bed Length	GAWR or GCAWR	Floor	No. Axles	Ramp Gate	Tilt-Bed	Slide Out Ramps	Side Rail Height	Coupler Ball Size	Tires	Electric Brakes	Surge Brakes
UT48AE	4'	8'	2,000 lbs.	1" Treated Wood	1		X		12"	2"	ST 5.30X12" LRC	NA	NA
UT58AE	5'	8'	2,000 lbs.	1" Treated Wood	1		X		12"	2"	ST 5.30X12" LRC	NA	NA
UT48A	4'	8'	3,500 lbs.	1" Treated Wood	1		X		16"	2"	ST205/75/D 14" LRC	optional	optional
UT58A	5'	8'	3,500 lbs.	1" Treated Wood	1		X		16"	2"	ST205/75/D 14" LRC	optional	optional
UT510A	5'	10'	3,500 lbs.	1" Treated Wood	1		X		16"	2"	ST205/75/D 14" LRC	optional	optional
UT6410A	6'-4"	10'	3,500 lbs.	1-1/2" Treated Wood	1		X		16"	2"	ST205/75/D 14" LRC	optional	optional
UT6412A	6'-4"	12'	3,500 lbs.	1-1/2" Treated Wood	1		X		16"	2"	ST205/75/D 14" LRC	optional	optional
UT6414AT	6'-4"	14'	7,000 lbs.	1-1/2" Treated Wood	2			X	16"	2 5/16"	ST205/75/D 14" LRC	1 axle Std.	optional
UT6416AT	6'-4"	16'	7,000 lbs.	1-1/2" Treated Wood	2			X	16"	2 5/16"	ST205/75/D 14" LRC	1 axle Std.	optional
LT48AE	4'	8'	2,000 lbs.	1-1/2" Treated Wood	1	X			12"	2"	ST 5.30X12" LRC	NA	NA
LT58AE	5'	8'	2,000 lbs.	1-1/2" Treated Wood	1	X			12"	2"	ST 5.30X12" LRC	NA	NA
LT48A	4'	8'	3,500 lbs.	1" Treated Wood	1	X			16"	2"	ST205/75/D 14" LRC	optional	optional
LT58A	5'	8'	3,500 lbs.	1" Treated Wood	1	X			16"	2"	ST205/75/D 14" LRC	optional	optional
LT510A	5'	10'	3,500 lbs.	1" Treated Wood	1	X			16"	2"	ST205/75/D 14" LRC	optional	optional
LT6410A	6'-4"	10'	3,500 lbs.	1" Treated Wood	1	X			16"	2"	ST205/75/D 14" LRC	optional	optional
LT6412A	6'-4"	12'	3,500 lbs.	1-1/2" Treated Wood	1	X			16"	2"	ST205/75/D 14" LRC	optional	optional
LT6414AT	6'-4"	14'	7,000 lbs.	1-1/2" Treated Wood	2	X			16"	2 5/16"	ST205/75/D 14" LRC	1 axle Std.	optional
LT6416AT	6'-4"	16'	7,000 lbs.	1-1/2" Treated Wood	2	X			16"	2 5/16"	ST205/75/D 14" LRC	1 axle Std.	optional

CONTACT:



MASTER TOW

783 Slocomb Road
 Fayetteville, NC 28311
 (910) 630-2000 • 1-800-522-2190
 Fax (910) 630-2016
 Email: mastertow@mastertow.com
 Web: www.mastertow.com