

tubular STEEL



Models: UT48, UT410, UT58, UT510, LT48, LT410, LT58, LT510 (LT58 shown)

4' & 5' wide models: available in 8' & 10' bed lengths. LT models feature a fold-down landscape gate. UT models feature a tilt-bed.
Standard features: 16" high sides, tip-away tongue jack, 3,500 lb. GAWR, 14" tires & wheels, 1" thick treated wood floor, 8 tie down points
Available options: 24" high sides, metal mesh on sides and front, brakes



Models: UT6410, UT6412, UT6414, LT6410, LT6412, LT6414 (LT6410 shown)

6'-4" wide single axle models: available in 10', 12' and 14' bed lengths. LT models feature a fold-down landscape gate. UT models feature a tilt-bed.
Standard features: 16" high sides, tip-away tongue jack, 3,500 lb. GAWR, 14" tires & wheels, 1-1/2" thick treated wood floor, 8 tie down points
Available options: 24" high sides, metal mesh on sides and front, brakes, 6'-10" wide bed



Models: UT6412T, UT6414T, UT6416T, LT6410T, LT6412T, LT6414T, UT6416T (LT6416T shown)

6'-4" wide tandem axle models: available in 12', 14', 16', 18', 20', 22', & 24' bed lengths. LT models feature a fold-down landscape gate. UT models feature slide-out ramps.
Standard features: 16" high sides, tip-away tongue jack, 7,000 lb. GCAWR, 1 electric brake axle, 14" tires & wheels, 1-1/2" thick treated wood floor, 8 tie down points
Available options: 24" high sides, metal mesh on sides and front, 2nd brake axle, 10,000 lb. GCAWR package, 6'-10" wide bed



Models: CH6416, CH61016, FFCH6416, FFCH61016, 18, 20, 22, 24 (FFCH61016 shown)

6'-4" & 6'-10" wide Car Haulers: available in 16', 18', 20', 22', & 24' bed lengths. CH models feature an open center. FFCH models feature a full floor. Both models have slide-out ramps, light protectors, and 4 heavy duty D-ring tie down points.
Standard features: tip-away jack, 7,000 lb. GCAWR, 1 electric brake axle, 14" tires & wheels, 1/8" steel diamond plate floor.
Available options: stake pockets, spare tire & wheel mount, winch mount, 2nd brake axle, 10,000 lb. GCAWR package, 6'-10" wide bed



Models: MT583R, MT6103R (MT6103R shown)

5' & 6'-10" wide Motorcycle Trailers: available in 8' & 10' bed lengths. MT models feature a drop axle, fold-down loading ramp, 3 bike runners, light protectors, and multiple tie down points.
Standard features: 35" long swing-up loading ramp, tip-away tongue jack, 3,500 lb. GAWR, 14" tires & wheels, 16 Ga. diamond plate steel floor, 6-1/2" wide runners
Available options: spare tire & wheel mount, brakes

Tubular Steel Trailer Features



A



B



C



D



E



F

- A** 4 Heavy Duty Tie Down Points On Each Side
- B** Easy To Use Spring Loaded Gate Latch
- C** Slide-Out Ramps & Protected Lighting
- D** Tip-Away Jack Mounted To Tubular A-Frame Tongue
- E** Pressure Treated Wood Flooring Boards
- F** Computer Balanced 14" Tires & Wheels

Model	Bed Width	Bed Length	GAWR or GCAWR	Floor	No. Axles	Ramp Gate	Tilt-Bed	Slide Out Ramps	Side Rail Height	Coupler Ball Size	Tires	Electric Brakes	Surge Brakes
UT48	4'	8'	3,500 lbs.	1" Treated Wood	1		X		16"	2"	ST205/75/D 14" LRC	optional	optional
UT58	5'	8'	3,500 lbs.	1" Treated Wood	1		X		16"	2"	ST205/75/D 14" LRC	optional	optional
UT510	5'	10'	3,500 lbs.	1" Treated Wood	1		X		16"	2"	ST205/75/D 14" LRC	optional	optional
UT6410	6'-4"	10'	3,500 lbs.	1-1/2" Treated Wood	1		X		16"	2"	ST205/75/D 14" LRC	optional	optional
UT6412	6'-4"	12'	3,500 lbs.	1-1/2" Treated Wood	1		X		16"	2"	ST205/75/D 14" LRC	optional	optional
UT6414T	6'-4"	14'	7,000 lbs.	1-1/2" Treated Wood	2			X	16"	2 5/16"	ST205/75/D 14" LRC	1 axle Std.	optional
UT6416T	6'-4"	16'	7,000 lbs.	1-1/2" Treated Wood	2			X	16"	2 5/16"	ST205/75/D 14" LRC	1 axle Std.	optional
LT48	4'	8'	3,500 lbs.	1" Treated Wood	1	X			16"	2"	ST205/75/D 14" LRC	optional	optional
LT58	5'	8'	3,500 lbs.	1" Treated Wood	1	X			16"	2"	ST205/75/D 14" LRC	optional	optional
LT510	5'	10'	3,500 lbs.	1" Treated Wood	1	X			16"	2"	ST205/75/D 14" LRC	optional	optional
LT6410	6'-4"	10'	3,500 lbs.	1-1/2" Treated Wood	1	X			16"	2"	ST205/75/D 14" LRC	optional	optional
LT6412	6'-4"	12'	3,500 lbs.	1-1/2" Treated Wood	1	X			16"	2"	ST205/75/D 14" LRC	optional	optional
LT6414T	6'-4"	14'	7,000 lbs.	1-1/2" Treated Wood	2	X			16"	2 5/16"	ST205/75/D 14" LRC	1 axle Std.	optional
LT6416T	6'-4"	16'	7,000 lbs.	1-1/2" Treated Wood	2	X			16"	2 5/16"	ST205/75/D 14" LRC	1 axle Std.	optional
CH6416	6'-4"	16'	7,000 lbs.	11Ga. Steel Plate	2			X	NA	2 5/16"	ST205/75/D 14" LRC	1 axle Std.	optional
CH61016	6'-10"	16'	7,000 lbs.	11Ga. Steel Plate	2			X	NA	2 5/16"	ST205/75/D 14" LRC	1 axle Std.	optional
FFCH6416	6'-4"	16'	7,000 lbs.	11Ga. Steel Plate	2			X	NA	2 5/16"	ST205/75/D 14" LRC	1 axle Std.	optional
FFCH61016	6'-10"	16'	7,000 lbs.	11Ga. Steel Plate	2			X	NA	2 5/16"	ST205/75/D 14" LRC	1 axle Std.	optional
MT583R	5'	8'	3,500 lbs.	16Ga. Steel Plate	1	X			NA	2"	ST205/75/D 14" LRC	optional	optional
MT6103R	6'-10"	10'	3,500 lbs.	16Ga. Steel Plate	1	X			NA	2"	ST205/75/D 14" LRC	optional	optional

CONTACT:



MASTER TOW

783 Slocomb Road
 Fayetteville, NC 28311
 (910) 630-2000 • 1-800-522-2190
 Fax (910) 630-2016
 Email: mastertow@mastertow.com
 Web: www.mastertow.com